

SolarEdge Home Hub Inverter Single Phase, for Europe / India / Philippines

SE2200H / SE3000H / SE3680H / SE4000H / SE5000H /
SE6000H / SE8000H / SE10000H



Single phase inverter for storage and backup applications, with MultiRange Concept – one part number for all power classes

- /// The ultimate home energy manager in charge of PV production, battery storage, backup operation during a power outage*, and smart energy devices
- /// Integrates seamlessly with the complete SolarEdge Home ecosystem, through the SolarEdge Home Network
- /// One part number for all power classes, streamlining every step:
 - /// Unified product configuration simplifies ordering, logistics, and inventory
 - /// Optimized system design, selection, and installation
- /// Record-breaking up to 99% weighted efficiency with up to 200% DC oversizing
- /// Small, lightweight, and easy to install
- /// Module-level monitoring and full visibility of battery status, PV production, and self-consumption data
- /// A scalable solution that supports future homeowner needs through easy connection to a growing ecosystem of products

* Backup applications are subject to local regulations and require a connection to the SolarEdge Home Batteries and the SolarEdge Home Backup Interface.

/ SolarEdge Home Hub Inverter

Single Phase, for Europe / India / Philippines

SE2200H / SE3000H / SE3680H / SE4000H / SE5000H / SE6000H /
SE8000H / SE10000H

Applicable to inverters with part number	SE10000H-RWSKBF57 ⁽¹⁾								Units
	SE2200H	SE3000H	SE3680H	SE4000H	SE5000H	SE6000H	SE8000H	SE10000H	
OUTPUT – AC ON GRID									
Rated AC Power	2200	3000	3680	4000	5000 ⁽²⁾	6000 ⁽²⁾	8000	10,000	VA
Maximum AC Power Output	2200	3000	3680	4000	5000 ⁽²⁾	6000 ⁽²⁾	8000	10,000	VA
AC Output Voltage (Nominal)	220 – 230 / 240								Vac
AC Output Voltage (Range)	184 – 264.5								Vac
AC Frequency Range (Nominal)	50 / 60 ± 5								Hz
Maximum Continuous Output Current RMS	10	14	16	18.5	23	27.5	36.5	45.5	A
Fault Current Protection (100ms)	40						70		A
Total Harmonic Distortion (THD)	< 3								%
Power Factor	1, adjustable -0.9 to 0.9						1, adjustable -0.8 to 0.8		
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes								
Charge Battery from AC (if allowed)	Yes								
Typical Nighttime Power Consumption	< 2.5								W
OUTPUT – AC BACKUP									
@50Hz	Maximum AC Power in Backup Operation	10,000 ⁽³⁾							W
	AC Frequency	50 ± 5							Hz
	Maximum Continuous Output Current in Backup Operation	45.5							A
	Fault Current Protection (100ms)	70							A
	AC Output Voltage (Nominal)	220 – 230							Vac
@60Hz	Maximum AC Power in Backup Operation	12,500 ⁽⁴⁾							W
	AC Frequency	60 ± 5							Hz
	Maximum Continuous Output Current in Backup Operation	52							A
	Fault Current Protection (100ms)	74							A
	AC Output Voltage (Nominal)	240							Vac
AC Output Voltage (Range)	184 – 264.5							Vac	
INPUT – DC (PV AND BATTERY)									
Transformer-less, Ungrounded	Yes								
Maximum Input Voltage	480								Vdc
Nominal DC Input Voltage	380								Vdc
Ground-Fault Isolation Detection	600kΩ Sensitivity per Unit								
Maximum DC PV Power	4400	6000	7360	8000	10,000	12,000	16,000	20,000	W
Maximum Input Current	6.5	9.0	10.5	11.5	13.5	16.5	20.5	25.5	Adc
Maximum Inverter Efficiency	99.2								%
European Weighted Efficiency	98.3	98.8			99				%
Reverse-Polarity Protection	Yes								

(1) On-site commissioning to selected power rating using SolarEdge Go. For details about the inverters approved for installation in your country, see [here](#).

(2) 4600 VA AC / 7130 VA DC in Germany.

(3) The default AC power in backup operation for each model is equal to its rated AC power in on-grid mode. The AC power in backup operation is selectable within the range of 3,000W to 10,000W for all models. Ensure that the protective device and CSA of the cable are correct for the selected power in backup mode.

(4) Operational only at ambient temperatures up to 30°C. Above 30°C, the Maximum AC Power in Backup Operation is 11,400W.

/ SolarEdge Home Hub Inverter

Single Phase, for Europe / India / Philippines

SE2200H / SE3000H / SE3680H / SE4000H / SE5000H / SE6000H /
SE8000H / SE10000H

Applicable to inverters with part number	SE10000H-RWSKBF57 ⁽¹⁾								Units
	SE2200H	SE3000H	SE3680H	SE4000H	SE5000H	SE6000H	SE8000H	SE10000H	
BATTERY STORAGE									
Supported Battery Models	SolarEdge Home Battery 400V								
Number of Batteries per Inverter	Up to 3								
Continuous Power	5000W per battery, total continuous discharge power is limited up to the inverter rated AC power for on-grid and backup applications								W
SMART ENERGY CAPABILITIES									
Backup and Battery Storage	With Backup Interface (purchased separately) for service up to 100A; up to 3 SolarEdge single phase inverters								
POWER OPTIMIZER COMPATIBILITY									
Supported Power Optimizers	1:1 Power Optimizers only, of the following types: SolarEdge S-Series, SolarEdge P-Series, SolarEdge OP-Series ⁽⁵⁾								
ADDITIONAL FEATURES									
Supported Communication Interfaces	RS485; Ethernet; Wi-Fi (optional); LTE (optional); SolarEdge Home Network								
Integrated AC, DC and Communication Connection Unit	Built-in								
Inverter Commissioning	Inverter Commissioning with the SolarEdge Go mobile application using built-in Wi-Fi Access Point for local connection								
STANDARD COMPLIANCE									
Safety	IEC 62109; IS 16221-2								
Grid Connection Standards	VDE-AR-N 4105, Tor Erzeuger Typ A, EN 50549-1, CEI 0-21 G98 Type A, G98 NI Type A, RD 1699 / RD 413 / NTS, VDE-V 0126-1-1, VFR 2019, C10/11, G100, IS 16169, IEC 61683, IEC 62116, IEC 61727								
Electromagnetic Compatibility (EMC)	IEC 61000-6-2, IEC 61000-6-3, EN/IEC 61000-3-2, EN/IEC 61000-3-3, IEC 61000-3-11, IEC 61000-3-12, EN 55011								
INSTALLATION SPECIFICATIONS									
Warranty	12 (standard) / extendable up to 25 (optional) years, with an 8-year warranty applicable to systems installed in India ⁽⁷⁾								
AC Output – Supported Cable Diameter	9 – 16								mm
AC – Supported Wire Cross Section	1 – 13								mm ²
Dimensions with Connection Unit (H x W x D)	535 x 370 x 185								mm
DC Input	3 x MC4 pairs for PV input; 1 x MC4 pair for battery input								
Weight	19.6								kg
Cooling	Natural convection								
Noise	< 25								dBA
Operating Temperature Range	-40 to +60								°C
Protection Rating	IP65 – outdoor and indoor								

(5) OP-Series Power Optimizers are allowed for PV-only installations. For OP-Series Power Optimizer compatibility for storage installations, contact your local SolarEdge representative or SolarEdge support.

(6) For specific warranty details of the SolarEdge Home Hub Single Phase Inverter in India, refer to the [SolarEdge Limited Product Warranty \(India\)](#).

SolarEdge is a global leader in smart energy technology. By leveraging world-class engineering capabilities and with a relentless focus on innovation, SolarEdge creates smart energy solutions that power our lives and drive future progress.

SolarEdge developed an intelligent inverter solution that changed the way power is harvested and managed in photovoltaic (PV) systems. The SolarEdge DC optimized inverter maximizes power generation while lowering the cost of energy produced by the PV system.

Continuing to advance smart energy, SolarEdge addresses a broad range of energy market segments through its PV, storage, EV charging, UPS, and grid services solutions.

-  SolarEdge
-  @SolarEdgePV
-  @SolarEdgePV
-  SolarEdgePV
-  SolarEdge
-  www.solaredge.com/corporate/contact

solaredge.com

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREEDGE, the SolarEdge logo, OPTIMIZED BY SOLAREEDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: April 29, 2026 DS-000279-ROW Subject to change without notice.

Cautionary Note Regarding Market Data and Industry Forecasts: This brochure may contain market data and industry forecasts from certain third-party sources. This information is based on industry surveys and the preparer's expertise in the industry and there can be no assurance that any such market data is accurate or that any such industry forecasts will be achieved. Although we have not independently verified the accuracy of such market data and industry forecasts, we believe that the market data is reliable and that the industry forecasts are reasonable.

